



*Industrial Products, Inc.*  
 PO Box 68004, Indianapolis, IN 46268

317.872.5806 | 317.875.5649 Fax  
 www.bhindust.com | sales@bhindust.com

## Flexible Screw Conveyor - Quotation Form

Ingredient		Particle size	
Ingredient bulk density	____ lbs./ft <sup>3</sup>	Flowability	Free <input type="checkbox"/> Sluggish <input type="checkbox"/> Very poor <input type="checkbox"/>
Conveyor length	__ ft. horiz. x __ ft. vertical	Area classification	NEMA 12 <input type="checkbox"/> NEMA 4 <input type="checkbox"/> NEMA 4X <input type="checkbox"/> Class __ Div __ Grp ____

Hoppers	Basic Hopper	Bolted Lid	Hinged Lid
3.5 ft <sup>3</sup>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
8 ft <sup>3</sup>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
12 ft <sup>3</sup>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Hopper level sensing	NEMA 4	NEMA 4X	NEMA 7/9
Rotary type	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Proximity type	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Hopper vibrator	<input type="checkbox"/>		
Flanged inlets	Horizontal	30°	45°
6" x 9" opening, 304 SS	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Control Panels	NEMA 12 Dust tight, painted steel enclosure.	NEMA 4 Water tight, painted steel enclosure.	NEMA 4X Water tight, fiberglass <sup>1</sup> enclosure.	NEMA 7/9 Explosion proof for Class I & II, Div I & II.
Basic control panel	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Vibrator control adder	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Speed control adder <sup>2</sup>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Comments:

---



---



---



---

<sup>1</sup> SS panels are available.

<sup>2</sup> VFD can be supplied separately.